

# Eaton FF500

Catalog Number: FF500

Fuse-link, LV, 500 A, AC 690 V, BS88/C2, 74 x 210 mm, gL/gG, BS



## General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	FF500  UPC 051712839907
EAN	Product Length/Depth
5027590019880	209 mm
Product Height	Product Width
74 mm	74 mm
Product Weight	Warranty
1034 g	Not Applicable
Compliances	
RoHS Compliant	

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

general industrial applications

### Amperage Rating

500 A

### Fitted with:

Centre bolted tags

### Fuse size

BS88/C2

### Current type

AC/DC

### Mounting dimension

M10

### Center-to-center distance of connections

185 mm

### Breaking capacity

80 kA

### Rated switching capacity

80 kA

### Rated voltage AC

690 V

### Rated voltage DC

400 V

### Class

Class gG/gL

### Fuse type

FF

### Utilization category

gG (cable protection/equipment protection)

### Color

None

### Interrupt rating

80 kAIC

### Fuse indicator

## Resources

### Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA CD CD100M FF FG GG GF GH

CE CD CD100M FF FG GG GF GH

### Multimedia

Eaton Bussmann - Red Spot fuse links

### Technical data sheets

4102 FF fuses

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

38 W

Connection

133/184 mm fixing centre

Construction

BS88/C2

Construction size

C2

Fuse shape

Center bolted tags

Voltage type

AC/DC

Voltage rating

690 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)