

Eaton FF630

Catalog Number: FF630

Fuse-link, low voltage, 630 A, AC 690 V, DC 400 V, BS88/C2, 74 x 210 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage	FF630
British standard fuse	UPC
	051712839921
EAN	Product Length/Depth
5027590019927	209 mm
Product Height	Product Width
74 mm	74 mm
Product Weight	Warranty
1051 g	Not Applicable
Compliances	
RoHS Compliant	

Electrical rating

Amperage Rating

630 A

Breaking capacity

80 kA

Interrupt rating

80 kAIC

Rated switching capacity

80 kA

Voltage rating

690 V

Voltage type

AC/DC

Physical details

Color

None

Fuse type

FF

General information

Class

Class gG/gL

Connection

133/184 mm fixing centre

Construction size

C2

Fitted with:

Centre bolted tags

Fuse indicator

None

Fuse shape

Center bolted tags

Fuse size

BS88/C2

Insulated metal gripping lugs (IMGL)

No

Utilization category

gG (cable protection/equipment protection)

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA CD CD100M FF FG GG GF GH](#)

[CE CD CD100M FF FG GG GF GH](#)

Technical data sheets

[4102 FF fuses](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)