

# Eaton FNQ-R-12

Catalog Number: FNQ-R-12

Eaton Bussmann series FNQ-R fuse, 12 A, Class CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 200 kAIC, Melamine tube, Standard, 600 V



General specifications

|                                    |                |
|------------------------------------|----------------|
| Product Name                       | Catalog Number |
| Eaton Bussmann series FNQ-R fuse   | FNQ-R-12       |
| Model Code                         | UPC            |
| CLASS CC TIME DELAY REJECTION FUSE | 051712497107   |
|                                    | EAN            |
|                                    | 5027590092265  |
| Product Length/Depth               | Product Height |
| 0.41 in                            | 1.5 in         |
| Product Width                      | Product Weight |
| 0.41 in                            | 0.15 lb        |
| Warranty                           | Compliances    |
| Not Applicable                     | CE Marked      |
|                                    | RoHS Compliant |

## Electrical Ratings

### Amperage Rating

12 A

### Voltage rating

600 V

## General Information

### Application

Line protection, small control transformers, industrial control, branch circuits

### Connection

Ferrule end x ferrule end

### Special features

Rejection style

## Physical Details

### Type

Current-limiting high inrush time-delay fuse

## Resources

### Catalogs

[Bussmann series complete full line catalog no. 1007](#)

### Multimedia

[Bussmann series Fuseology](#)

### Specifications and datasheets

[Eaton Specification Sheet - FNQ-R-12](#)

### Technical data sheets

[FNQ-R-12~CLASS CC TIME DELAY REJECTION FUSE](#)

### Technical service bulletins

[Datasheet - FNQ-30](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)