Eaton FWP-100G22F

Catalog Number: FWP-100G22F

Eaton Bussmann series FWP high speed fuse, 690V, 100A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications



Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWP-100G22F

UPC

051712689731

EAN

5027590500081

Product Length/Depth

58 mm

Product Height

Froduct rieigni

22 mm

Product Width

22 mm

Product Weight

50.9 g

Warranty
No warranty

Compliances

Certifications

CE Marked

UL Recognized

RoHS Compliant

IEC Rated





Product specifications

Fuse indicator Other Interrupt rating 200 kAIC Construction size 22 mm x 58 mm Clearing (I2T) 10300 Connection Ferrule end x ferrule end Material Ceramic Release characteristic Other **Amperage Rating** 100 A Frequency rating - max 62 Hz Utilization category gR (general purpose semiconductor protection) Watt losses 17.7 W Fuse type FWP-G22F Accessories CH22 Modular fuse holder Type High speed fuse Fuse shape Cylindrical Breaking capacity 200 kA Fuse size

22 x 58 mm

Frequency rating - min

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE High-speed, cylindrical gR fuse-links

UKCA High-speed, cylindrical gR fuse-links

Technical data sheets

10469 22 x 58 mm gR cylindrical fuse links

45 Hz

Class

Class gR

Pre arc (I2T)

2065

Voltage rating

500 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia