

# Eaton FWP-40A22F

Catalog Number: FWP-40A22F

Eaton Bussmann series FWP high speed fuse, 700 Vac (IEC), 700 Vdc (UL), 40A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



## General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-40A22F
UPC	051712796552
EAN	Product Length/Depth
5027590500739	58 mm
Product Height	Product Width
23 mm	23 mm
Product Weight	Warranty
59.9 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

## Product specifications

Interrupt rating	Catalogs
200 kAIC	IEC high speed fuse links
Release characteristic	Bussmann series complete full line catalog no. 1007
Other	Compliance information
Amperage Rating	UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc
40 A	CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc
Frequency rating - max	
62 Hz	
Fuse type	
FWP-A22F	
Accessories	
JM70100 Fuse base	
Minimum melting	
68 I <sub>2</sub> t (A2 sec)	
Fuse size	
22 x 58 mm	
Voltage rating	
700 V	
Fuse indicator	
Other	
Construction size	
22 mm x 58 mm	
Clearing (I <sub>2</sub> T)	
960	
Color	
White	
Connection	
Ferrule end x ferrule end	
Quantity	
10	
Material	
Ceramic	
Utilization category	
aR (accompanied semiconductor protection)	

## Resources

**Watt losses**

12 W

**Type**

High speed fuse

**Fuse shape**

Cylindrical

**Used with**

Finger safe holders/blocks and striker

**Breaking capacity**

200 kA

**Frequency rating - min**

45 Hz

**Class**

Class aR

**Pre arc (I<sub>2T</sub>)**

68

**Application**

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

**Voltage type**

AC/DC

**Packaging type**

Standard