

Eaton FWP-90B

Catalog Number: FWP-90B

Eaton Bussmann series FWP high speed fuse, 250 Vac/dc, 90A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-90B
	UPC
	051712796033
EAN	Product Length/Depth
5027590021883	112 mm
Product Height	Product Width
25 mm	25 mm
Product Weight	Warranty
108 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

[Type](#)

High speed fuse

[Application](#)

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

[Amperage Rating](#)

900 A

[Breaking capacity](#)

200 kA

[Fuse indicator](#)

Non Indicating

[Insulated metal gripping lugs \(IMGL\)](#)

No

[Utilization category](#)

aR (accompanied semiconductor protection)

[Voltage type](#)

AC/DC

[Rated switching capacity](#)

200 A

[Rated voltage AC](#)

700 V

[Rated voltage DC](#)

700 V

[Mounting dimension](#)

M8

[Center-to-center distance of connections](#)

91.5 mm

[Current type](#)

AC/DC

[Class](#)

Class aR

[Clearing \(I²T\)](#)

2700 at 700 V

[Watt losses](#)

25 W

[Catalogs](#)

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

[Technical data sheets](#)

[FWP NA bolted fuse-links](#)

Fuse shape

Center bolted tags

Pre arc (I2T)

415

Color

None

Interrupt rating

50 kAIC at 700 Vdc

200 kAIC Vac

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia