

# Eaton FWX-30A14F

Catalog Number: FWX-30A14F

Eaton Bussmann series FWX high speed fuse, 600V, 30A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

## General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-30A14F
UPC	051712795609
EAN	Product Length/Depth
5027590501392	55 mm
Product Height	Product Width
32 mm	73 mm
Product Weight	Warranty
20.2 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	

## Product specifications

### Fuse indicator

Non Indicating

### Interrupt rating

200 kAIC

### Construction size

14 mm x 51 mm

### Clearing (I<sub>2</sub>T)

500 at 250 V

### Connection

Ferrule end x ferrule end

### Material

Ceramic

### Release characteristic

Other

### Amperage Rating

2 A

### Frequency rating - max

62 Hz

### Utilization category

aR (accompanied semiconductor protection)

### Watt losses

5.9 W

### Fuse type

FWX-A14F

### Accessories

CH14 Modular fuse holder

FW14-PCB

### Type

High speed fuse

### Fuse shape

Cylindrical

### Breaking capacity

200 kA

### Fuse size

14 x 51 mm

## Resources

### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

### Technical data sheets

720006 FWX

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I<sub>2T</sub>)

100

Voltage rating

690 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia