

Specifications



Eaton JM60060-3MW14

Eaton Bussmann series JM modular fuse block, Multi-Wire load-side lug, 60 A, 3P, 120°C, 50 lb-inches max, Class J, CVR(I)-J-60060, Black, Box lug, 200 kAIC, 75 °C, Stranded, Panel, DIN rail, 600 V

General specifications

PRODUCT NAME	Eaton Bussmann series JM modular fuse block
CATALOG NUMBER	JM60060-3MW14
UPC	051712620642
PRODUCT LENGTH/DEPTH	3.7 in
PRODUCT HEIGHT	2.6 in
PRODUCT WIDTH	4.5 in
PRODUCT WEIGHT	0.7125 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	600 V

General information

ACCESSORIES	CVR(I)-J-60060
CONNECTION	Box lug
MOUNTING METHOD	Panel DIN rail
SPECIAL FEATURES	Multi-Wire Load-Side Lug

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class J
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C

Resources

	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CATALOGS	Bussmann series complete full line catalog no. 1007 JM60060-3MW14~FUUSE BLK, J 600V 60A 3P
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2201
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - JM60060-3MW14



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

