

Specifications



Photo is representative

Eaton MV155F2DCX125E

Eaton Bussmann series MV055 E-Rated medium voltage fuse, Current limiting, 125A, 50 kAIC Symmetrical Maximum interrupt rating, E class, Silver ribbon element, Fiberglass tube, 2 barrels, 0.75 in diameter, 21.7 in length

General specifications

PRODUCT NAME	Eaton Bussmann series MV155F E-rated fuse
CATALOG NUMBER	MV155F2DCX125E
UPC	051712552868
PRODUCT LENGTH/DEPTH	0.75 in
PRODUCT HEIGHT	23 in
PRODUCT WIDTH	0.75 in
PRODUCT WEIGHT	24 lb
WARRANTY	Not Applicable
COMPLIANCES	Contact factory
CERTIFICATIONS	ANSI



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	125 A
INTERRUPT RATING	50 kAIC
VOLTAGE RATING	15.5 kV

General information

BARRELS	2
CLASS	Class E
CONNECTION	Ferrule end x ferrule end
ELEMENT	Silver ribbon
FUSE INDICATOR	Non Indicating

Physical details

MATERIAL	Fiberglass tube
PACKAGING TYPE	Standard

Resources

CATALOGS

[Bussmann series 2018 full line catalog no. 1007, section 7 - medium voltage fuses](#)

[Bussmann series complete full line catalog no. 1007](#)

[MV155F2DCX125E~MEDIUM VOLTAGE E-RATED](#)

MULTIMEDIA

[Bussmann series Fuseology](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - MV155F2DCX125E](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

