

Specifications



Eaton OPM-1038RSW

Eaton Bussmann series Optima fuse holders, 30 A (UL/CSA), Three-pole, 100 kA, #8-18 AWG stranded, #10-18 AWG solid, 100 kAIC, Thermoplastic, 600 V (UL/CSA), Use with 13/32 Inches X 1-1/2 Inches, KTK, FNM, FNQ

General specifications

PRODUCT NAME	Eaton Bussmann series Optima fuse holders
CATALOG NUMBER	OPM-1038RSW
UPC	051712797719
PRODUCT LENGTH/DEPTH	0.001 in
PRODUCT HEIGHT	0.001 in
PRODUCT WIDTH	0.001 in
PRODUCT WEIGHT	0.8125 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	Contact Manufacturer UL Listed CSA Certified



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	30A (UL/CSA)
INTERRUPT RATING	100 kAIC
SHORT-CIRCUIT RATING	100 kA
VOLTAGE RATING	600 V (UL/CSA)

General information

CONNECTION	#10-18 AWG solid #8-18 AWG stranded
USED WITH	For use with 13/32 In X 1- 1/2 In KTK, FNM, FNQ Non- Rejection fuse

Physical details

MATERIAL	Thermoplastic
NUMBER OF POLES	Three-pole

Resources

MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - OPM-1038RSW Bussmann series OPM-1038 non-switch fuse holder no. 1102
TECHNICAL DATA SHEETS	Bussmann series OPM-1038 switch fuse holder no. 1103 OPM-1038RSW-OPTIMA MODULE W/SWITCH
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

