

Specifications



Photo is representative



Eaton RD100-3-SCCR

Eaton Bussmann series RD non-fused rotary disconnect switch, Standard switch, Front handle operation, 600 Vac, 250 Vdc, 100A, Non-fused disconnect switch

General specifications

PRODUCT NAME	Eaton Bussmann series RD non-fused rotary disconnect switch
CATALOG NUMBER	RD100-3-SCCR
UPC	051712402422
PRODUCT LENGTH/DEPTH	11 in
PRODUCT HEIGHT	6.5 in
PRODUCT WIDTH	11 in
PRODUCT WEIGHT	5.32 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable RoHS Compliant



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	100A
VOLTAGE RATING	600 Vac, 250 Vdc

Physical details

OPERATING TEMPERATURE - MAX	70 °C
OPERATING TEMPERATURE - MIN	-20 °C

Resources

CATALOGS	RD100-3-SCCR~Switch 100A Non-F 3P UL98 Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RD100-3-SCCR

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

