

Technical data sheet

Cable fittings and accessories

LÜTZE CABLEFIX® Vario

Blank plugs

Feed-through for all prefabricated cables and wires with connectors



Identification

Type	VARIO BL8
Part No.	606254

Product version

Datasheet version	00
-------------------	----

Use/Application/Properties

Application	• Electrotechnology, pneumatics, hydraulics, robotics, general machine and plant construction
Properties	• Blank plugs for feed through and terminal frames • High flexibility in the application • Additional mounting to existing installation easily possible • Even pressure effect on the feed through round material yields good strain relief and sealing • Unneeded holes in the module can simply with blank plugs • Very good weathering resistance
Description	• Blank plug, PA6 GF15

Technical data

Length	30 mm
Temperature range	-40 °C ... +125 °C
Degree of protection	IP65
Diameter D	8 mm
suitable for Part-No.	606155

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

21.12.2022 • Subject to technical modification

Part No. [606254](#) • Datasheet version: 00

page 1 of 2

Technical data sheet

Cable fittings and accessories

Construction

Description	LÜTZE CABLEFIX® VARIO BL8
Material	PA 6 GF 15
Material characteristics	UV-resistant ozone-resistant Oil resistant fuel-resistant acid-resistant. alkali-resistant solvent-resistant seawater-resistant

General

PU (units)	1
------------	---