

Specifications



Eaton WPMV7L-UNV1-S903D

Eaton Crouse-Hinds series Champ WPMV LED wall pack, 0.21A, Cool white, Dimmable driver, 3/4" entry, 150-175W equiv, 50/60 Hz, Diffused polycarb lens, 7000 lm, 115 lm/W, Die cast alum, Yoke mt, 7x6 distribution, 120-277 Vac, 125-250 Vdc, 59W

Photo is representative



General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Champ WPMV LED wall pack light fixture
CATALOG NUMBER	WPMV7L-UNV1-S903D
UPC	662276892941
PRODUCT LENGTH/DEPTH	9.16 in
PRODUCT HEIGHT	12.76 in
PRODUCT WIDTH	12.6 in
PRODUCT WEIGHT	14 lb
PRODUCT TYPE	LED wall pack light fixture

Certifications and compliances

AREA CLASSIFICATION	Ordinary/Non-Hazardous Locations
STANDARDS TYPE	NEC/CEC
NEMA RATING	4X
INGRESS PROTECTION (IP) RATINGS	IP66

Product specifications

LAMP TYPE	LED
LUMENS	7000
LUMENS PER WATT	115
COLOR TEMPERATURE	Cool white
OPTICAL DISTRIBUTION	7x6
MOUNTING METHOD	Yoke
VOLTAGE RATING	120-277 Vac, 125-250 Vdc
FREQUENCY RATING	50/60 Hz
LENS MATERIAL	Diffused polycarbonate
WATTAGE	59 W
AMPERAGE RATING	0.21 A
POWER FACTOR	> 0.90
DIMMING	Dimmable driver
ENTRY SIZE	3/4"
MATERIAL	Die cast aluminum
EQUIVALENT LUMINAIRE	150-175W

Resources

3D MODELS	SP3D Design Package - Champ Pro WPMV LED Industrial Wallpack Light Fixtures
BROCHURES	Crouse-Hinds series industrial LED lighting solutions Crouse-Hinds series Global LED lighting portfolio Crouse-Hinds series WPMV LED brochure
CATALOGS	Crouse-Hinds series Champ WPMV LED catalog page
INSTALLATION INSTRUCTIONS	IF 1893 - Champ-Pak WPMVL LED Wall Pack
SPECIFICATIONS AND DATASHEETS	Crouse-Hinds series Champ WPMV LED IES photometric files Eaton Specification Sheet - WPMV7L-UNV1-S903D

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

