



6266HG



6265HGC



5369NHG



8115GY

Hospital Specification Grade Straight Blade Plugs & Connectors

2-Pole, 3-Wire Grounding
15A, 125V/AC
NEMA 5-15



5-15P



5-15R

Hospital Grade Plugs & Connectors

Safety Grip™ NEMA 5-15



Rating A V/AC	Product Type & Cord Diameter	Body Color	Plug	Catalog No.	Connector
15 125	● Straight Body 0.33-0.66" (7.6-16.7mm)	Black & White	☐ 6266HG	●	☐ 6269HG
	● Straight Body 0.33-0.66" (7.6-16.7mm)	Clear	☐ 6266HGC	●	☐ 6269HGC
	● Angled Body 0.33-0.66" (7.6-16.7mm)	Black & White	☐ 6265HG	●	—
	● Angled Body 0.33-0.66" (7.6-16.7mm)	Clear	☐ 6265HGC	●	—

AutoGrip™ NEMA 5-15



Rating A V/AC	Product Type & Cord Diameter	Body Color	Plug	Catalog No.	Connector
15 125	● Straight Body 0.33-0.66" (7.6-16.7mm)	Black & White	☐ 5266NHG	●	☐ 5269NHG
	● Isolated Ground, Straight Body 0.33-0.66" (7.6-16.7mm)	Orange	☐ IG5266NHG	●	—

QuickGrip™ NEMA 5-15



Rating A V/AC	Product Type & Cord Diameter	Body Color	Plug	Catalog No.	Connector
15 125	● Straight Body 0.22-0.66" (5.6-16.8mm)	Gray	☐ 8115GY	●	—

Hospital Specification Grade Straight Blade Plugs & Connectors

2-Pole, 3-Wire Grounding
20A, 125V/AC
NEMA 5-20



5-20P



5-20R

Hospital Grade Plugs & Connectors

Safety Grip™ NEMA 5-20



Rating A V/AC	Product Type & Cord Diameter	Body Color	Plug	Catalog No.	Connector
20 125	● Straight Body 0.33-0.66" (7.6-16.7mm)	Black & White	☐ 6766HG	●	☐ 6769HG
	● Angled Body 0.33-0.66" (7.6-16.7mm)	Black & White	☐ 6765HG	●	—
	● Angled Body 0.33-0.66" (7.6-16.7mm)	Clear	☐ 6765HGC	●	—

AutoGrip™ NEMA 5-20



Rating A V/AC	Product Type & Cord Diameter	Body Color	Plug	Catalog No.	Connector
20 125	● Straight Body 0.33-0.66" (7.6-16.7mm)	Black & White	☐ 5366NHG	●	☐ 5369NHG

Hospital Grade Dimensional
Information: B-18

Specification Information:

Safety Grip HG Plugs &
Connectors: B-25

AutoGrip HG Plugs &
Connectors: B-25

QuickGrip HG Plugs &
Connectors: B-25

Icon Key

● Hospital Grade Device

NAFTA Compliant - see page O-30

Hospital Specification Grade Plugs & Connectors

2-Pole, 3-Wire Grounding
15A, 125V/AC; 15A, 250V/AC; 20A, 125V/AC; 20A, 250V/AC
NEMA 5-15, 6-15, 5-20, 6-20

	Device Type	Hospital Grade Safety Grip™ Plugs & Connectors, Straight Blade	Hospital Grade AutoGrip™ Plugs & Connectors, Straight Blade	Hospital Grade QuickGrip™ Plugs & Connectors, Straight Blade
	Wiring Type	Back wire	Back wire	Back wire
	Testing & Code Compliance	• Listed to UL498, file no. E3663	• Listed to UL498, file no. E3663	• Listed to UL 498, file no. E146159
		• Complies with Federal Spec. WC-596F	• Complies with Federal Spec. WC-596F	• UL verified to Federal Spec. WC-596F
• cUL certified to C22.2, no. 42-M1999		• cUL certified to C22.2, no. 42-M1999	• cUL certified to C22.2, no. 42	
Specifications: Environmental	Flammability	Meets UL94 requirements; V2 rated	Meets UL94 requirements; V2 rated	Meets UL94 requirements; V2 rated
	Temperature Rating	-40°C to 75°C (-40°F to 167°F)	-40°C to 75°C (-40°F to 167°F)	-40°C to 75°C (-40°F to 167°F)
Specifications: Electrical	Dielectric Voltage	Withstands 1500V per UL498	Withstands 1500V per UL498	Withstands 1500V per UL498
	Current Interrupting	Yes, at full-rated current	Yes, at full-rated current	Yes, at full-rated current
	Temperature Rise	Max. 30°C (86°F) after 250 cycles of overload	Max. 30°C (86°F) after 250 cycles of overload	Max. 30°C (86°F) after 250 cycles of overload
Specifications: Mechanical	Terminal Accommodation	#12 - #18 AWG	#12 - #18 AWG	#12 - #18 AWG
	Voltage Ratings	Permanently marked on device	Permanently marked on device	Permanently marked on device
Materials:	Plug/Connector Outer Shell	Nylon; polycarbonate on C version	Nylon; polycarbonate on C version	Nylon
	Interior Body	Nylon	Nylon	Nylon
	Terminal Retainer	Polycarbonate	Polypropylene	N/A
	Blades	0.065” thick brass	0.065” thick brass	0.060” thick brass
	Line Contacts	0.031” thick brass	0.031” thick brass	0.032” thick brass
	Terminal Clamps	Galvanized steel	Galvanized steel	Brass
	Terminal Screws	#8-32 brass, nickel plated	#8-32 brass, nickel plated	#8-32 steel, hot screw brass plated
	Ground Screw	#8-32 brass, green	#8-32 brass, green	#8-32 steel (green)
	Assembly/ Mounting Screws	Steel	Steel	Steel
	Cord Clamp	Nylon	Polypropylene	Nylon
	Gasket/Dust Shield	EPDM	EPDM	N/A