

Specifications



Photo is representative

Eaton RM25060-3CHR

Eaton Bussmann Series RM modular fuse block, Box Lugs with hex screws, 60 A, 3P, 120°C, 50 lb-inches max, Class R, CVR(I)-RH-25060, Black, 200 kAIC, 75 °C, Stranded, DIN rail, Panel, 250 V, #2-14 AWG

General specifications

PRODUCT NAME	Eaton Bussmann Series RM modular fuse block
CATALOG NUMBER	RM25060-3CHR
UPC	051712620857
PRODUCT LENGTH/DEPTH	4 in
PRODUCT HEIGHT	4.2 in
PRODUCT WIDTH	4 in
PRODUCT WEIGHT	0.57 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	250 V

General information

ACCESSORIES	CVR(I)-RH-25060
CONNECTION	Box lug
MOUNTING METHOD	DIN rail Panel
SPECIAL FEATURES	Box Lugs with Hex Screws

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class R
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	#2-14 AWG

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 RM25060-3CHR~FUSE BLK, R 250V 60A 3P
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2202
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RM25060-3CHR



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.