

Specifications



Photo is representative

Eaton RM60060-3MW24

Eaton Bussmann Series RM power distribution fuse block, 60 A, 3P, R, Black, Box lug, 200 kA, 75°C, Stranded, DIN rail, Panel, 600 V, Line: #6 AWG Cu, Load: (2)#12-16 AWG Cu, Line: (2) #10 AWG Cu, Load: #8-16 AWG Cu

General specifications

PRODUCT NAME	Eaton Bussmann Series RM power distribution fuse block
CATALOG NUMBER	RM60060-3MW24
UPC	051712621007
PRODUCT LENGTH/DEPTH	4.5 in
PRODUCT HEIGHT	8 in
PRODUCT WIDTH	4.5 in
PRODUCT WEIGHT	0.8075 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	600 V

General information

CONNECTION	Box lug
MOUNTING METHOD	Panel DIN rail
SPECIAL FEATURES	Multi-Wire Line-Side & Load-Side Lugs

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class R
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	Line: (2) #10 AWG Cu Load: (2)#12-16 AWG Cu Load: #8-16 AWG Cu Line: #6 AWG Cu

Resources

CATALOGS	RM60060-3MW24-FUSE BLK, R 600V 60A 3P Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2202
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RM60060-3MW24



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.