

## Applications:

- Aircraft fueling and maintenance areas
- Oil and gas exploration and production
- Grain and sugar milling, processing and storage
- Fuel dispensing facilities
- Petrochemical facilities
- Coal processing and storage
- Munitions manufacturing and storage
- Marine and watertight requirements
- Paint and formulation facilities
- Pipeline compressor/pumping and storage
- Alcohol formulation, blending and storage

## Features:

- May be locked into the ON or OFF position for added safety
- Heavy duty mounting pads
- Silicone lubricant provided for cover screws and flange
- Flametight, close tolerance threaded switch stem
- 20 amperes single-pole, two-pole, three-way and four-way units
- 20 or 30 amperes single-pole double throw and two-pole double throw options

## Certifications and compliances:

- Class I, Divisions 1 & 2, Groups C, D
- Class II, Divisions 1 & 2, Groups E, F, G
- UL1203
- Conforms to IP65
- ABS

## Standard materials:

- Box and cover – cast copper-free aluminum
- Switch stem – stainless steel
- Hardware – stainless steel

## Technical specifications:

- Entries – one 1/2" NPT (standard); up to 3/4" NPT through feed available (optional)
- Voltage – 120-277 VAC

## Mounting option:

- Surface mount, via two 5/16" maximum mounting bolts (not included)



## Entry options:

| NPT trade size | Dead end | Through feed |
|----------------|----------|--------------|
| 1/2"           | Std.     | C1           |
| 3/4"           | E2       | C2           |

## Ordering information:

| Cat. #       | Description                               | Weight (lbs.) |
|--------------|-------------------------------------------|---------------|
| EPCS2211A    | Single-pole, 20A                          | 4.5           |
| EPCS2212A    | Two-pole, 20A                             | 4.5           |
| EPCS2212A-30 | Two-pole, 30A                             | 4.5           |
| EPCS2214A    | Three-way, 20A                            | 4.5           |
| EPCS2215A    | Four-way, 20A                             | 4.5           |
| EPCS2216A    | Single-pole double throw (ON), 30A        | 4.5           |
| EPCS2217A    | Single-pole double throw (ON/OFF/ON), 20A | 4.5           |
| EPCS2218A    | Two-pole double throw (ON/OFF/ON), 20A    | 4.5           |
| EPCS2219A    | Two-pole double throw (ON), 30A           | 4.5           |

## Dimensions (in inches):

