

Eaton FCF40RN

Catalog Number: FCF40RN

Eaton Bussmann series FCF fuse, 40 A, 60 Hz, 50 Hz, 1 , CF, Black, Non-indicating, Electroless tin plated copper alloy terminal, Blade end|Class CF, 6 min at 200%, 300 kAIC at 600 V|50 kAIC at 600 Vdc, Glass filled PES, 600 V, 600 Vdc

General specifications

| | |
|--------------------------------|----------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series FCF fuse | FCF40RN |
| UPC | Product Length/Depth |
| 051712362504 | 2.13 in |
| Product Height | Product Width |
| 1.9 in | 1 in |
| Product Weight | Warranty |
| 0.17 lb | Not Applicable |
| Compliances | Certifications |
| CE Marked | UL Listed |
| RoHS Compliant | CSA Certified |



Electrical rating

Amperage Rating

40 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac

50 kAIC at 600 Vdc

Response time

6 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH60N, CCP2-3-60CF

Resources

Catalogs

FCF40RN-Fast Acting CUBEFuse 40A Non-indication

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

The Power of Space

Specifications and datasheets

Eaton Specification Sheet - FCF40RN



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)