

Eaton FCF60RN

Catalog Number: FCF60RN

Eaton Bussmann series FCF fuse CUBEFuse, Finger safe, power loss 7.27 w, Critical/UPS, 60 A, 60 Hz, 50 Hz, 1 , CF, Black, Blade end, 6 min at 200%, 50 kAIC at 600 Vdc|300 kAIC at 600 V, Glass filled PES

General specifications

Product Name	Catalog Number
Eaton Bussmann series FCF fuse	FCF60RN
UPC	Product Length/Depth
051712362535	2.13 in
Product Height	Product Width
1.9 in	1 in
Product Weight	Warranty
0.17 lb	Not Applicable
Compliances	Certifications
CE Marked	UL Listed
RoHS Compliant	CSA Certified



Electrical rating

Amperage Rating

60 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac

50 kAIC at 600 Vdc

Response time

6 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH60N, CCP2-3-60CF

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

[FCF60RN~Fast Acting CUBEFuse 60A Non-indication](#)

Multimedia

[Bussmann series Fuseology](#)

[The Power of Space](#)

Specifications and datasheets

[Eaton Specification Sheet - FCF60RN](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)