

Eaton FWH-25A14F

Catalog Number: FWH-25A14F

Eaton Bussmann series FWH high speed fuse, 25A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWH-25A14F
	Model Code
	500V 25A S/COND FERRULE 14 X 51MM
UPC	EAN
051712370837	5027590499590
Product Length/Depth	Product Height
55 mm	32 mm
Product Width	Product Weight
73 mm	20.4 g
Warranty	Compliances
Not Applicable	CE Marked RoHS Compliant
Certifications	
UL Recognized CSA Certified	



Product specifications

Fuse indicator

Other

Interrupt rating

50 kAIC

Construction size

14 mm x 51 mm

Clearing (I2T)

191 at 500 V

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

25 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

7 W

Fuse type

FWH-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

14 x 51 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720008 FWH

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

49

Voltage rating

600 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)