

Eaton FWH-30A14F

Catalog Number: FWH-30A14F

Eaton Bussmann series FWH high speed fuse, 1000 Vac, 800 Vdc, 30A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

| | |
|---|-----------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series high speed cylindrical fuse | FWH-30A14F |
| | UPC |
| | 051712370844 |
| EAN | Product Length/Depth |
| 5027590499620 | 55 mm |
| Product Height | Product Width |
| 32 mm | 73 mm |
| Product Weight | Warranty |
| 20.4 g | Not Applicable |
| Compliances | Certifications |
| CE Marked | CSA Certified |
| RoHS Compliant | UL Recognized |



Product specifications

Fuse indicator

Other

Interrupt rating

50 kAIC

Construction size

14 mm x 51 mm

Clearing (I2T)

232 at 500 V

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

30 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

9 W

Fuse type

FWH-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

14 x 51 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Specifications and datasheets

Eaton Specification Sheet - FWH-30A14F

Technical data sheets

720008 FWH

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

58

Voltage rating

500 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)