

# Eaton FWP-30B

Catalog Number: FWP-30B

Eaton Bussmann series FWP high speed fuse, 1400 Vac (FWS 8-15A), 2100 Vac (FWS 2-6A), 1000 Vdc (FWL/FWS 2-30A), 30A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed cylindrical fuse	FWP-30B
	UPC
	051712557832
<b>EAN</b>	<b>Product Length/Depth</b>
5027590500593	73 mm
<b>Product Height</b>	<b>Product Width</b>
15 mm	15 mm
<b>Product Weight</b>	<b>Warranty</b>
24.8 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
RoHS Compliant	CSA Certified



## Product specifications

### Rated voltage DC

700 V

### Interrupt rating

50 kAIC at 700 Vdc

200 kAIC Vac

200 kAIC at 300 Vdc

50 kAIC at 300 Vdc

### Center-to-center distance of connections

63.35 mm

### Insulated metal gripping lugs (IMGL)

No

### Current type

AC/DC

### Mounting method

Stud

### Amperage Rating

30 A

### Fuse type

FWP-B

### Fuse system (according to IEC 60269)

Other

### Rated switching capacity

200 A

### Fuse size

14 x 51 mm

### Voltage rating

700 Vac, 700 Vdc (UL)

### Fuse indicator

Non Indicating

### Construction size

Other

### Clearing (I2T)

450 at 700 V

### Rated voltage AC

700 V

### Color

## Resources

### Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

### Specifications and datasheets

[Eaton Specification Sheet - FWP-30B](#)

None

#### Connection

Blade end x blade end

#### Mounting dimension

M6

#### Utilization category

aR (accompanied semiconductor protection)

#### Watt losses

9 W

#### Type

High speed fuse

#### Fuse shape

Center bolted tags

#### Breaking capacity

200 kA

#### Class

Class aR

#### Pre arc (I2T)

58

#### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

#### Voltage type

AC/DC

#### Packaging type

Standard