

# Eaton FWP-40A14FI

Catalog Number: FWP-40A14FI

Eaton Bussmann series FWP high speed fuse, 690 Vac (IEC), 700 Vac (UL), 600 Vdc (UL), 40A, 200 kAIC at 700 Vac, 50 kAIC at 600 Vdc, With Indicator, High speed fuse, Female end X ferrule end, Class aR, White, Ceremic

## General specifications



| Product Name                                      | Catalog Number       |
|---|----------------------|
| Eaton Bussmann series high speed cylindrical fuse | FWP-40A14FI          |
|   | UPC                  |
|   | 051712542852         |
| EAN   | Product Length/Depth |
| 5027590500722                                     | 52 mm                |
| Product Height                                    | Product Width        |
| 15 mm   | 15 mm                |
| Product Weight                                    | Warranty             |
| 20.4 g  | Not Applicable       |
| Compliances                                       | Certifications       |
| CE Marked   | UL Recognized        |
| RoHS Compliant                                    | CSA Certified        |

## Product specifications

|   |   |
|---|---|
| Interrupt rating                          | Catalogs  |
| 200 kAIC                                  | IEC high speed fuse links                           |
| Release characteristic                    | Bussmann series complete full line catalog no. 1007 |
| Other                                     | Compliance information                              |
| Amperage Rating                           | UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc   |
| 40 A                                      | CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc     |
| Frequency rating - max                    | Specifications and datasheets                       |
| 62 Hz                                     | Eaton Specification Sheet - FWP-40A14FI             |
| Fuse type                                 | Technical data sheets                               |
| FWP-A14FI                                 | 720025 FWP  |
| Fitted with:                              |   |
| Striker                                   |   |
| Fuse size                                 |   |
| 14 x 51 mm                                |   |
| Voltage rating                            |   |
| 700 V                                     |   |
| Fuse indicator                            |   |
| Top fuse status indicator                 |   |
| Construction size                         |   |
| 14 mm x 51 mm                             |   |
| Clearing (I <sub>2</sub> T)               |   |
| 750                                       |   |
| Color                                     |   |
| White                                     |   |
| Connection                                |   |
| Ferrule end x ferrule end                 |   |
| Quantity                                  |   |
| 10  |   |
| Material                                  |   |
| Ceramic                                   |   |
| Utilization category                      |   |
| aR (accompanied semiconductor protection) |   |
| Watt losses                               |   |
| 8 W                                       |   |

## Resources

**Type**

High speed fuse

**Fuse shape**

Cylindrical

**Used with**

Finger safe holders/blocks and striker

**Breaking capacity**

200 kA

**Frequency rating - min**

45 Hz

**Class**

Class aR

**Pre arc (I<sub>2T</sub>)**

84

**Application**

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

**Voltage type**

AC/DC

**Packaging type**

Standard



Eaton Corporation plc

Eaton House

30 Pembroke Road  
Dublin 4, Ireland

Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia