

Eaton FWP-40G14F

Catalog Number: FWP-40G14F

Eaton Bussmann series FWP high speed fuse, 690V, 40A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end - FWP-40G14F

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-40G14F
	UPC
	051712689533
EAN	Product Length/Depth
5027590500777	51 mm
Product Height	Product Width
14 mm	14 mm
Product Weight	Warranty
19.2 g	No warranty
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated



Product specifications

Fuse indicator

Other

Interrupt rating

200 kAIC

Construction size

14 mm x 51 mm

Clearing (I2T)

1331

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

40 A

Frequency rating - max

62 Hz

Utilization category

Other

Watt losses

7.52 W

Fuse type

FWP-G14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

14 x 51 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE High-speed, cylindrical gR fuse-links

UKCA High-speed, cylindrical gR fuse-links

Specifications and datasheets

Eaton Specification Sheet - FWP-40G14F

Technical data sheets

10468 14 x 51 mm gR cylindrical fuse links

Frequency rating - min

45 Hz

Class

Class gR

Pre arc (I2T)

211

Voltage rating

690 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia