

Eaton GDA-200MA

Catalog Number: GDA-200MA

Eaton GDA Series Fast-acting fuse 0.200, 250 Vac, 32 Vdc (self certified), GDA-200MA

General specifications

Product Name	Catalog Number
Eaton Bussmann series GDA fast-acting fuse	GDA-200MA
Product Length/Depth	Product Height
20 mm	5 mm
Product Width	Product Weight
5 mm	1 g
Compliances	Certifications
CE Marked	VDE
CCC Marked	Catalog Notes
	High breaking capacity



Product specifications

Fuse indicator

Non-indicating

Interrupt rating

1.5 kAIC at 250 Vac

Connection

Ferrule end x ferrule end

Quantity

5

Material

Ceramic tube

Silver-plated endcap construction

Melting (I₂T)

Typical: 0.02 A

Amperage Rating

0.200

Voltage drop

1350 mV typical

Frequency rating - max

50 Hz

Resistance

6 ohms DC cold

Type

Electronic

Frequency rating - min

50 Hz

Voltage rating

250 Vac, 32 Vdc (self certified)

Application

Electronic circuits

Resources

Specifications and datasheets

[Eaton Specification Sheet - GDA-200MA](#)

[Eaton GDA fast-acting fuse data sheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)