

# Eaton GDA-630MA

Catalog Number: GDA-630MA

Eaton GDA Series Fast-acting fuse 0.630A, 250 Vac, 32 Vdc (self certified), GDA-630MA

## General specifications

Product Name	Catalog Number
Eaton Bussmann series GDA fast-acting fuse	GDA-630MA
Product Length/Depth	Product Height
20 mm	5 mm
Product Width	Product Weight
5 mm	0.002 kg
Compliances	Certifications
CE Marked	VDE
CCC Marked	Catalog Notes
	High breaking capacity



## Product specifications

### Fuse indicator

Non-indicating

### Interrupt rating

1.5 kAIC at 250 Vac

### Connection

Ferrule end x ferrule end

### Quantity

5

### Material

Ceramic tube

Nickel-plated brass end cap construction

### Melting (I<sub>2</sub>T)

Typical: 0.064 A

### Amperage Rating

0.630A

### Voltage drop

1200 mV typical

### Frequency rating - max

50 Hz

### Resistance

0.34 ohms DC cold

### Type

Electronic

### Frequency rating - min

50 Hz

### Voltage rating

250 Vac, 32 Vdc (self certified)

### Application

Electronic circuits

## Resources

### Specifications and datasheets

[Eaton Specification Sheet - GDA-630MA](#)

[Eaton GDA fast-acting fuse data sheet](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)