



Representative Image

Catalog No. 9T10A1003**Description: "3A,45kVA,480-208Y,150C,N2,K1,DOE"****UPC No 783173904435****Home > Transformers > Dry Type Vented > General Purpose**

ABB's Low Voltage Dry Type transformers are built to last and are designed with exclusive features. With easy installation and all of the specifications you trust, it's easy to see why ABB QL dry type transformers are preferred by contractors. Our Type QL transformers meet DOE efficiency standards. They are available with aluminum or copper windings and in all three temperature rise ratings.

Descriptors

| | |
|-------------|-----------------|
| Category | General Purpose |
| GO Schedule | TY |

Specifications

| | |
|------------------|----------|
| TransType | DOE 2016 |
| Phase | 3 |
| PriVoltage | 480 |
| SecVoltage | 208Y/120 |
| KVA | 45.0 KVA |
| Coil Material | AL |
| TempRise | 150.0 °C |
| Frequency | 60 Hz |
| Impedance | 4.3 % |
| AmbTemp | 40.0 °C |
| EnergyEfficiency | DOE 2016 |
| KFactor | K1 |
| Enclosure Type | NEMA 2 |
| Sound | Std |

Classifications

| | |
|----|---|
| CE | 0 |
|----|---|