![ABB](ABB logo)



Representative Image

# Catalog No. TH3363JR

**Description: 100A 3P HD N3R/5/12 600V FUSIBLE**

**UPC No 783164064032**

**Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

When it comes to getting the job done right, you can count on safety switches from ABB. ABB offers a wide variety of general duty switches for residential and light commercial purposes, while the extensive line of heavy-duty switches is best suited for commercial and industrial applications. For the toughest industrial environments — such as cement foundries, steel mills and processing plants — dust-tight and stainless steel switches are available. We also offer a variety of double throw switches for emergency generators. No matter the application, we've got you covered with a rugged, reliable and easy-to-install Spec-Setter safety switch. 100A 3P HD N3R/5/12 600V FUSIBLE

## Descriptors

| | |
|---|---|
| Category | Heavy Duty |
| GO Schedule | S1 |

## Specifications

| | |
|---|---|
| Voltage | 600 AC |
| Amperage | 100 A |
| Poles | 3 |
| Wires | 3 |
| Fusing | Fusible |
| Enclosure | NEMA 3R,5,12 Outdr/Drp/Dst |
| Options | None |
| Wire Range (Cu/Al) | 10-1/0 |
| 480 Vac, NEC Std, 1-ph | 10.0 hp |
| 480 Vac, NEC Std, 3-ph | 25.0 hp |
| 480 Vac, Time Delay, 1-ph | 30.0 hp |
| 480 Vac, Time Delay, 3-ph | 60.0 hp |
| 600 Vac, NEC Std, 1-ph | 15.0 hp |
| 600 Vac, NEC Std, 3-ph | 30.0 hp |
| 600 Vac, Time Delay, 1-ph | 40.0 hp |
| 600 Vac, Time Delay, 3-ph | 75.0 hp |
| 250 Vdc | 20.0 hp |
| GSA Compliance | Yes |

## Classifications

| | |
|---|---|
| cUL Listed | Yes |
| UL Listed | Yes |

## Dimensions

| | |
|---|---|
| Height | 25.40 in |

## Dimensions

| | |
|---|---|
| Depth | 5.00 in |
| Width | 13.40 in |
| Weight | 38.0 lb |