

12/3C SOOW CAROLPRENE YLW

12/3C SOOW CAROLPRENE YLW



GENERAL INFO

Thermoset rubber cord products have evolved over the last 50 years from simple and unsophisticated to a product line where specialized, technologically advanced products are in demand for exacting commercial and industrial applications. No longer are rubber cord products used only in applications where flexibility is needed; today typical applications require cord to perform well in environments of extreme heat and cold and on job sites and factory floors where resistance to oil, chemicals and abrasion is mandatory. General Cable's role, as the producer of the premiere Carol® Brand rubber cord products, is to ensure that new product development, product innovation and quality not only keep pace with industry requirements but also set the trends. Our rubber cord products carry a full range of listings and certifications with Underwriters Laboratories, Inc. and the Canadian Standard Association. In addition, many products meet or exceed the requirements of OSHA, MSHA and other relevant industry standards. Carol Brand is simply the most accepted in the industry, having proven itself on the job time after time. Our rubber cord line is the most comprehensive in the industry, ensuring that the proper Carol product can always be specified.

PRODUCT RANGE GENERAL INFORMATION

Conductor material	Copper
Nominal voltage U [V]	600
Flame retardant	Yes
Oil resistant	Yes
Resistant to UV	Yes
Outdoor installation	Yes

ELECTRICAL PROPERTIES

Nominal operation capacitance [pF/ft]
Screen DC resistance [mOhm/ft]
Conductor resistance at 20° C [mOhm/ft]

STANDARDS AND APPROVALS



ITEM DETAILS

AWG size	12
Conductor category	Class 2 = stranded
Nominal outer diameter [inch]	0.595

PRODUCT PACKAGING

APPLICATION PROPERTIES

Product name	12/3C SOOW CAROLPRENE YLW
Conductor resistance at operation temperature [mOhm/ft]	
Nominal thickness insulation [inch]	0.045
Nominal outer diameter [inch]	0.595
Nominal operation capacitance [pF/ft]	
Screen DC resistance [mOhm/ft]	
Nominal thickness insulation [mm]	1.14
Nominal outer diameter [mm]	15.11