



Quality Products. Service Excellence.

IT, Security and Pro AV Rack Cabinet *RCK Series*

1,050 lbs (476 kg) Weight Capacity



We designed our RCK Cabinet series for your Homelab and Pro-AV applications. We've included numerous unique features, such as bonus rack units, compatibility with standard hardware components, and more. Every RCK is self-squaring and takes just minutes to assemble. In addition, each cabinet has mounting points for our easy four-screw field-installable doors.

Features

- Available in six (6) heights and two (2) depths.
- Optional locking doors are constructed in 16-gauge steel. The door(s) install in minutes and are available in solid, vented, and **acrylic window** options.
- Doors include a locking swing handle compatible with **electronic locking handles**.
- The ready-to-assemble self-squaring cabinet body is constructed in 16-gauge steel and includes vents for **optional fans** on the cabinet sides.
- Includes two (2) pairs of adjustable depth 10-32 threaded EIA-compliant rack rails.
- The cabinet's top and bottom rear feature a removable conduit knockout 1U panel. The top rear can be a bonus 1U rack mounting point for equipment or rack accessories.
- The front of the cabinet includes a steel plate at both the top and bottom. When removed reveals a Decora® compatible mounting point.
- Numerous cable tie-off points are included for front-to-rear cable management.
- The cabinet top includes solid top panel and conduit knockouts for additional cable entry.
- The cabinet base also includes mounting holes for optional **casters** or **leveling feet**.
- The top and cabinet bottom includes an opening compatible with interchangeable "1923" sized **top panels**.
- Cabinet ganging kit included.
- Includes 50-pack of **SCREW1032-50** screws.

Specifications

- The cabinet frame is constructed in 16-gauge steel.
- Mounting rails are constructed in 12-gauge steel.
- The top-Rear of the cabinet included 3.00", 2.50", and 2.0" knockouts for the conduit.
- Rear 1U panels include 1.375", 1.125", and 0.675" knockouts.
- Include multiple bonding and grounding points.
- 1,050 lbs (476 kg) **load rating**. Rolling caster load rated for up to 600 lbs (272 kg)
- Finished in textured RAL9005 black powder paint.
- TAA-compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America within an ISO 9001:2015 certified facility.

Gallery





Accessories

- Leveling Feet
- Rack Mount Basic PDU
- Rack Panels
- Protective Grommet Strip
- Locking Door
- Rack Shelves
- 10 AWG Bonding Wire Kits
- Latch Replacement Kit

Part No. Black	Overall Dimensions			Rack Units	Usable Mounting Dimensions		
	Height	Width	Depth		Height	Width	Depth
RCK12U25BK	26.38	24.00	25.00	12U + 1U	21.00	19.00	22.56
RCK18U25BK	36.50	24.00	25.00	18U + 1U	31.50	19.00	22.56
RCK20U25BK	40.00	24.00	25.00	20U + 1U	35.00	19.00	22.56
RCK24U25BK	47.00	24.00	25.00	24U + 1U	42.00	19.00	22.56
RCK36U25BK	68.00	24.00	25.00	36U + 1U	63.00	19.00	22.56
RCK42U25BK	78.50	24.00	25.00	42U + 1U	73.50	19.00	22.56
RCK12U32BK	26.38	24.00	32.00	12U + 1U	21.00	19.00	29.56
RCK18U32BK	36.50	24.00	32.00	18U + 1U	31.50	19.00	29.56
RCK20U32BK	40.00	24.00	32.00	20U + 1U	35.00	19.00	29.56
RCK24U32BK	47.00	24.00	32.00	24U + 1U	42.00	19.00	29.56
RCK36U32BK	68.00	24.00	32.00	36U + 1U	63.00	19.00	29.56
RCK42U32BK	78.50	24.00	32.00	42U + 1U	73.50	19.00	29.56

The +1U refers to the 1U usable accessory mounting at the top-rear of the cabinet.

Optional Doors

Use with Cabinet Height	Part No. Solid	Part No. Vented	Part No. Window
12U	RCKSD12UBK1	RCKVD12UBK1	RCKWD12UBK1
18U	RCKSD18UBK1	RCKVD18UBK1	RCKWD18UBK1
20U	RCKSD20UBK1	RCKVD20UBK1	RCKWD20UBK1
24U	RCKSD24UBK1	RCKVD24UBK1	RCKWD24UBK1
36U	RCKSD36UBK1	RCKVD36UBK1	RCKWD36UBK1
42U	RCKSD42UBK1	RCKVD42UBK1	RCKWD42UBK1

Optional Mounting Rails

Part No. Threaded 10-32	Part No. Square Hole	Usable Mounting Dimensions		Overall Cabinet
		Rack Units	Height	Width
H1TRR12U24BK	H1SRR12U24BK	12U	21.00	24.00
H1TRR18U24BK	H1SRR18U24BK	18U	31.50	24.00

Part No. Threaded 10-32	Part No. Square Hole	Usable Mounting Dimensions		Overall Cabinet Width
		Rack Units	Height	
H1TRR20U24BK	H1SRR20U24BK	20U	35.00	24.00
H1TRR24U24BK	H1SRR24U24BK	24U	42.00	24.00
H1TRR36U24BK	H1SRR36U24BK	36U	63.00	24.00
H1TRR42U24BK	H1SRR42U24BK	42U	73.50	24.00

Optional Casters

Part No.	Strength	Style/ Material	Overall Height		Hole Mounting Pattern		Caster Set	Qty	Qty with
			Wheel Diameter	Added to Cabinet	Width	Depth	Weight Capacity	Included In Set	Brakes Included
1425BLSOFT	Light Duty	Soft Thermoplastic	2.95	3.50	1.75	3.00	660 lbs (299 kg)	4	4
1425BM	Medium Duty	Hard Composition	3.00	3.81	1.75	3.00	700 lbs (318 kg)	4	0
1425BH	Heavy Duty	Hard Composition	3.00	3.81	1.75	3.00	1,050 lbs (476 kg)	4	0
1425BHLOCK	Heavy Duty	Hard Composition	3.00	3.81	1.75	3.00	1,050 lbs (476 kg)	4	4

Top/Bottom Panel Options

Part No.	Description	Fan Quantity	Fan Size	Thermostat		Cable Entry
				CFM	dB	
C2T1923SBK1	Solid (Included with Cabinet)	0	-	-	-	No
C2T1923VBK1	Vented	0	-	-	-	No
C2T1923VCEBK1	Vented with Cable Entry	0	-	-	-	No
C2T1923VFBK1	Fan Grill for Fan or Venting	4 (Fan Grill Only)	4.70	-	-	No
C2T1923FBK1	Cutout for Fan or Cable Entry	4 (Opening Only)	4.70	-	-	No
C2T1923F10BK1	Pre-Wired 1x 10 inch Fan	1	10.00	550	60	No
C2T1923F10CEBK1	Pre-wired fan with cable entry grommets	1	10.00	550	60	No
C2T1923F4BK1	Pre-wired 4x 4 inch fans	4	4.70	400	64	No
C2T1923F4TBK1	Pre-wired fans with thermostat	4	4.70	400	64	Yes

These panels work on both the top and bottom of the cabinet.

What's Inside the Box

Qty Included	Description	Replacement Part No.
1	RCK Body - Top	
1	RCK Body - Bottom	
2	RCK Body - Side Panel	
2	Pair of 10-32 Threaded Adjustable Rails	H1R Series
1	Solid Top/Bottom Panel with Hardware	C2T1923SBK1
2	1U Knockout Panel with Hardware	
8	Door Hinge Cover Plate with Hardware	
2	Decora Cover Plate with Hardware	
16	Rail Mounting Hardware (Spring-Nut and Bolt)	1421SN
16	M6 Cabinet Assembly Hardware	
2	Ganging Brackets	
50	10-32 x 0.75in Rack Mounting Screws	SCREW1032-50
1	Assembly Instructions	BUL88117

Note that levelling feet and/or casters are sold separately.

Data subject to change without notice

