



Representative

Catalog Number: CTPA10-S/100M
Product ID: 7TCA298000R0032
EAN Number: 05020963022692
Status: Active

Lightweight Weight, Extra Flexible Slit Conduit, NC Size 10/NW Size 8.5, Outside Diameter 10.0mm, Inside Diameter 8.7mm, Static Bend Radius 15mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Slit Lightweight Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications
Standard	RoHS, Conforms with End of Life Vehicle Directive (ELV)EU200/53/EC
Trade Size	NC10/NW8.5
Outside Diameter	10.0mm
Inside Diameter	8.7mm
Length	100 m
Radius	Static Bend Radius 15mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	10mm
Nominal size in inch	1/4 inch
Outer diameter	10mm
Inner diameter	8.7mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	Y
Halogen free	Y

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	4.51 lbs. Each

Header

3D Model Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289

