


Specification Sheet

Part Number: 111-01125



ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.

Inside serrations allows for strong grip on cables and wire bundles.

Head design provides high tensile strength with very low insertion force.

Article Number 111-01125

Type T120R

Color Blue (BU)

Quantity Per pack

Product Description ETFE ties provide excellent protection against radiation, ultraviolet light, and a wide range of chemicals. They are also rated for low outgassing applications. HellermannTyton's ETFE ties come in a standard color of blue for easy identification. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description High-Temp Cable Tie, 15" Long, UL Rated, 120lb Tensile Strength, ETFE, Blue, 50/pkg

Global Part Name T120R-E/TFE-BU

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 15.24

Length L (Metric) 387.0

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.29

Width W (Metric) 7.4

Bundle Diameter Min (Imperial) 0.2

Bundle Diameter Min (Metric) 5.0

Bundle Diameter Max (Imperial) 4.13

Bundle Diameter Max (Metric) 105.0

Thickness T (Imperial) 0.075

| | |
|----------------------------------|--|
| Thickness T (Metric) | 1.9 |
| Cable Tie Head Length (Imperial) | 0.41 |
| Cable Tie Head Width (Imperial) | 0.50 |
| Height H (Imperial) | 0.29 |
| Height H (Metric) | 7.35 |
| Material | Ethylenterafluoroethylene (E/TFE) |
| Material Shortcut | E/TFE |
| Flammability | UL 94 V-0 |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -112°F to +338°F (-80°C to +170°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL ANSI/UL 62275 UL ANSI/UL 746B UL ANSI/UL 1565 |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 50 |

Package Quantity (Metric) 50

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)