



STRIPPING LENGTH:

10mm (0.39 in.)

WIRE RANGE:

28-14 AWG, Solid / Stranded

#12 AWG Solid Cu (UL)

FLAMMABILITY:

UL94-V0

WORKING TEMP:

-30°C (-22°F) TO 85°C (185°F)

VOLTAGE:

450V (VDE) 85°C

600V (CULUS) 105°C

CERTIFICATIONS:

cULus, CE, ENEC, FIMKO, CQC

Revision level		
Drawing	State	Part
00.0	Design Release	-
Changed	Date (YYYY/MM/DD)	
JMC	20021/06/22	
Approved	Date (YYYY/MM/DD)	
JPG	2021/06/22	

Revision Record	
Revision level	Part
00.0	016553

All drawing revision are stored in CAD PDM database

The copyright of this drawing is reserved by HellermannTyton.

Drawn	Date (YYYY/MM/DD)
JMC	2021/06/22
Approved	Date (YYYY/MM/DD)
JPG	2021/06/22

HCRN-2 SERIES	
Title	Helacon Releasable Wire Connector, 2-port, Clear
Scale	2:1
Global Project Number	21-0275
Format	A3
Sheet	1/1

Units
mm
HellermannTyton
www.HellermannTyton.com

Drawing-No
21-0275-001-CSU