

## Specification Sheet

Part Number: 150-55610



Fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.

Fir Tree design provides low extraction and high extraction force.

1-Piece Cable Tie with Fir Tree Mount with Disc, 4.3"L, 0.19 - 0.20" Mounting Hole, PA66, Black, 500/pkg

|                |           |
|----------------|-----------|
| Article Number | 150-55610 |
|----------------|-----------|

|      |         |
|------|---------|
| Type | T18RDP5 |
|------|---------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. This is sold as an assembly with the cable tie. |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                          |
|-------------------|----------------------------------------------------------------------------------------------------------|
| Short Description | 1-Piece Cable Tie with Fir Tree Mount with Disc, 4.3"L, 0.19 - 0.20" Mounting Hole, PA66, Black, 500/pkg |
|-------------------|----------------------------------------------------------------------------------------------------------|

|                  |                 |
|------------------|-----------------|
| Global Part Name | T18RDP5-PA66-BK |
|------------------|-----------------|

|                                     |                          |
|-------------------------------------|--------------------------|
| Minimum Tensile Strength (Imperial) | 18                       |
| Minimum Tensile Strength (Metric)   | 80                       |
| Length L (Imperial)                 | 4.3                      |
| Length L (Metric)                   | 110.0                    |
| Fixation Method                     | Fir tree for round holes |
| Identification Plate Position       | none                     |
| Releasable Closure                  | No                       |
| Tie Closure                         | plastic pawl             |
| Variant                             | Inside Serrated          |
| Width W (Imperial)                  | 0.1                      |
| Width W (Metric)                    | 2.5                      |
| Bundle Diameter Min (Imperial)      | 0.06                     |
| Bundle Diameter Min (Metric)        | 1.5                      |
| Bundle Diameter Max (Imperial)      | 0.79                     |
| Bundle Diameter Max (Metric)        | 20.0                     |
| Thickness T (Imperial)              | 0.043                    |

|                                         |                      |
|-----------------------------------------|----------------------|
| Thickness T (Metric)                    | 1.1                  |
| Panel Thickness Min (Imperial)          | 0.12                 |
| Panel Thickness Max (Imperial)          | 0.16                 |
| Panel Thickness Min (Metric)            | 3.0                  |
| Panel Thickness Max (Metric)            | 4.0                  |
| Mounting Hole Diameter D (Imperial)     | 0.19 - 0.2 "         |
| Mounting Hole Diameter D (Metric)       | 4.9 - 5.1 mm         |
| Mounting Hole Diameter D Min (Imperial) | 0.19                 |
| Mounting Hole Diameter D Max (Imperial) | 0.2                  |
| Mounting Hole Diameter D Max (Metric)   | 5.1                  |
| Disc Diameter (Metric)                  | 13.0                 |
| Disc Diameter (Imperial)                | 0.5                  |
| Material                                | Polyamide 6.6 (PA66) |
| Material Shortcut                       | PA66                 |
| Flammability                            | UL 94 V-2            |

|                              |                                  |
|------------------------------|----------------------------------|
| UV Resistant (Yes/No)        | No                               |
| Use Conditions               | For Indoor and Outdoor Use       |
| Operating Temperature        | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
| Package Quantity (Imperial)  | 500                              |
| Package Quantity (Metric)    | 500                              |
| Customs Number               | 3926909988                       |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)