

Specification Sheet

Part Number: 151-00783



Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.

Extended fir tree allows for a wide range of panel thicknesses.

Fir tree design provides low insertion forces and high extraction forces.

Side Convoluted Tubing Clip, Max Bundle Diameter .6", PA66HIRHS, Black, 5000/pkg

Article Number	151-00783
----------------	-----------

Type	CTCFT6
------	--------

Color	Black (BK)
-------	------------

Quantity Per	carton
--------------	--------

Product Description	Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.
---------------------	--

Short Description	Side Convoluted Tubing Clip, Max Bundle Diameter .6", PA66HIRHS, Black, 5000/pkg
-------------------	--

Global Part Name	CTCFT6-PA66HIRHS-BK
------------------	---------------------

Length L (Imperial)	0.43
Length L (Metric)	11.0
Fixation Method	Fir Tree
Variant	Clips
Width W (Imperial)	0.43
Width W (Metric)	11.0
Bundle Diameter Min (Imperial)	0.43
Bundle Diameter Min (Metric)	11.0
Bundle Diameter Max (Imperial)	0.59
Bundle Diameter Max (Metric)	15.0
Height H (Imperial)	0.73
Height H (Metric)	18.5
Nominal Diameter (Imperial)	1.56
Nominal Diameter (Metric)	15.0
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.18

Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	4.5
Mounting Hole Diameter D (Imperial)	0.25 - 0.26
Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.7
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5003
Package Quantity (Metric)	5000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).