

Specification Sheet

Part Number: 151-04156



Saddle Mounts are designed to provide stability to wire bundles.

These mounts can accommodate miniature, intermediate or standard cross-section cable ties.

Built-in CutZone safety feature prevents damage to wires and cables.

Unique EZ Feed slot maintains clear space to insert cable ties.

Allows flexibility of frame size and mounting location with #10 (M5) screw into panel surface or with T-nut in frame.

Cable Tie Saddle Mount, 1.1 x 0.66", 0.2" Hole Dia, 0.33" Max Tie Width, PA66HS, Black, 100/bag

|                |            |
|----------------|------------|
| Article Number | 151-04156  |
| Type           | CTSM3CZS   |
| Color          | Black (BK) |
| Quantity Per   | bag        |

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description                 | Designed specifically for holding heavier cable bundles, these mounting bases can be used in many industries from agriculture to truck manufacturing. They mount securely and can be used with a wide variety of heavy duty cable ties up to 8.3 mm in width. Cables are held in place and aligned by troughs in the mount's arms. The EZ Feed cable tie slot eliminates common obstructions for faster completion. During rework, the CutZone prevents wire damage when cutting off cable ties. |
| Short Description                   | Cable Tie Saddle Mount, 1.1 x 0.66", 0.2" Hole Dia, 0.33" Max Tie Width, PA66HS, Black, 100/bag                                                                                                                                                                                                                                                                                                                                                                                                  |
| Global Part Name                    | CTSM3CZS-PA66HS-BK                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Length L (Imperial)                 | 1.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Length L (Metric)                   | 28.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Fixation Method                     | Screw Mounting and Rivet                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Width W (Imperial)                  | 0.66                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Width W (Metric)                    | 16.8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Height H (Imperial)                 | 0.46                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Height H (Metric)                   | 11.7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Cable Tie Width Max (Imperial)      | 0.33                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Cable Tie Width Max (Metric)        | 8.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Mounting Hole Diameter D (Imperial) | 0.21 "                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                                   |                                        |
|-----------------------------------|----------------------------------------|
| Mounting Hole Diameter D (Metric) | 5.35 mm                                |
| Material                          | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut                 | PA66HS                                 |
| Flammability                      | UL 94 V-2                              |
| Halogen Free                      | Yes                                    |
| UV Resistant (Yes/No)             | Yes                                    |
| Use Conditions                    | For Indoor Use Only                    |
| Operating Temperature             | -40°F to +257°F (-40°C to +125°C)      |
| BABA Compliant                    | YES                                    |
| Reach Compliant (Article 33)      | Yes                                    |
| ROHS Compliant                    | Yes                                    |
| UL Recognized (US)                | Yes                                    |
| UL Recognized (US and Canada)     | Yes                                    |
| Package Quantity (Imperial)       | 100                                    |
| Package Quantity (Metric)         | 100                                    |

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)