

Specification Sheet

Part Number: 151-04351

Long 6.5 mm fir tree allows clip to be installed in panels up to 6 mm thick and for hole sizes from 6.1-7.0 mm.

Fine-pitch ratchet provides controlled grip for a range of pipe sizes with one part.

Fully enclosed clamp prevents slip, crush and fallout under vacuum.

Release feature opens by inserting a screwdriver, allowing the clamp to be reused or serviced without removing it from mounting surface.



Ratchet O-Clamp, Fir Tree Mount, 0.73 - 0.89" Bundle Dia, 6.5 mm Hole Dia, PA66HIRHSUV, Black, 1000/ctn

Article Number	151-04351
Type	ROC18.5-22.5FT6.5
Color	Black (BK)
Quantity Per	pack
Product Description	The Ratchet O-Clamp is designed for tight spaces, maintaining a low profile while providing an adjustable closure for a range of bundle sizes. An integrated fir tree provides a secure grip into round mounting holes with no additional hardware.
Short Description	Ratchet O-Clamp, Fir Tree Mount, 0.73 - 0.89" Bundle Dia, 6.5 mm Hole Dia, PA66HIRHSUV, Black, 1000/ctn

Global Part Name	ROC18.5-22.5FT6.5-PA66HIRHSUV-BK
------------------	----------------------------------

Minimum Tensile Strength (Imperial)	100
-------------------------------------	-----

Minimum Tensile Strength (Metric)	445
-----------------------------------	-----

Length L (Imperial)	1.46
---------------------	------

Length L (Metric)	37.0
-------------------	------

Fixation Method	Fir Tree
-----------------	----------

Width W (Imperial)	0.81
--------------------	------

Width W (Metric)	20.5
------------------	------

Bundle Diameter Min (Imperial)	0.73
--------------------------------	------

Bundle Diameter Min (Metric)	18.5
------------------------------	------

Bundle Diameter Max (Imperial)	0.89
--------------------------------	------

Bundle Diameter Max (Metric)	22.5
------------------------------	------

Height H (Imperial)	1.81
---------------------	------

Height H (Metric)	46.0
-------------------	------

Panel Thickness Min (Imperial)	0.02
--------------------------------	------

Panel Thickness Max (Imperial)	0.24
--------------------------------	------

Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000

Package Quantity (Metric)	1000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)