

## Specification Sheet

Part Number: 151-04157



Temporarily holds wires along routing path until ready to make permanent.

Built-in CutZone safety feature prevents damage to wires and cables.

Unique EZ Feed slot maintains clear space to insert cable ties.

Allows flexibility of frame size and mounting location with #8 (M4) screw into panel surface or with T-nut in frame.

Article Number

151-04157

Type

CTCM6CZS

Color

Black (BK)

Quantity Per

bag

Product Description

The cradle mount with screw attachment fastens with a screw and T-nut and is ideal for routing wires in industrial applications where rework and adjustments are common. Mount features a 0.24" cradle opening for cable retention. The cradle arms can temporarily hold wires for simple adjustments and cable additions and protect against abrasion and cable damage. To permanently mount the bundle, the EZ Feed cable tie slot eliminates common obstructions for faster completion. During rework, the CutZone prevents wire damage when cutting off cable ties.

|                                     |  |
|-------------------------------------|--|
| Short Description                   | Cradle Mount With Screw Attachment, 0.24" Cradle Area, M4 Screw Hole Dia, PA66STHS, Black, 100/Pkg |
| Global Part Name                    | CTCM6CZS-PA66STHS-BK   |
| Length L (Imperial)                 | 1.0  |
| Length L (Metric)                   | 25.4   |
| Fixation Method                     | Screw Mounting and T-Nut   |
| Width W (Imperial)                  | 0.76   |
| Width W (Metric)                    | 19.3   |
| Height H (Imperial)                 | 0.55   |
| Height H (Metric)                   | 14.0   |
| Cable Tie Width Max (Imperial)      | 0.36   |
| Cable Tie Width Max (Metric)        | 9.07   |
| Mounting Hole Diameter D (Imperial) | 0.18   |
| Mounting Hole Diameter D (Metric)   | 4.5 mm   |
| Material                            | Polyamide 6.6, super tough, heat stabilized (PA66STHS)   |

|                              |                                   |
|------------------------------|-----------------------------------|
| Material Shortcut            | PA66STHS                          |
| Flammability                 | UL 94 HB                          |
| Halogen Free                 | Yes                               |
| UV Resistant (Yes/No)        | No                                |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 100                               |
| Package Quantity (Metric)    | 100                               |
| Customs Number               | 3926909988                        |