

Specification Sheet

Part Number: 596-12201



- Convenient tab is easier to remove from the liner, speeding labeling operations.
- Tab acts as a guide during positioning or repositioning to ensure a straight wrap and a high-quality appearance.
- Tab helps prevent label slippage when applied to cable insulation, reducing labor.
- In tests, TabTags increased the average number of wraps per hour by 12 percent, saving time and increasing output.

TabTags™ Thermal Transfer Tab Label, Self-Laminating, 1.0 x 0.5 x 1.56", Vinyl, White, 5M/RL

Article Number	596-12201
Type	TAG22T3ES
Color	White (WH)
Quantity Per	reel
Product Description	HellermannTyton TabTag thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. Handling the label by the tab helps keep fingers off the clear overlay, ensuring years of performance. The labels are UL recognized for indoor use with an aggressive acrylic adhesive that enables the label to bond to large and small diameter wires.

Short Description	TabTags™ Thermal Transfer Tab Label, Self-Laminating, 1.0 x 0.5 x 1.56", Vinyl, White, 5M/RL
Global Part Name	TAG22T3ES-100B-WH
Width W (Imperial)	1.0
Width W (Metric)	25.40
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.3
Bundle Diameter Max (Metric)	7.62
Height H (Imperial)	0.5
Height H (Metric)	12.7
Width of Liner (Metric)	85.09
Width of Liner (Imperial)	3.35
Material	Type 100B, Vinyl, white transparent, self-laminating (100B)
Material Shortcut	100B

Adhesive	Acrylic
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +205°F (-40°C to +96°C)
Operating Temperature	-40°F to +205°F (-40°C to +96°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3919102055
Labels per Row	3

