

Specification Sheet

Part Number: TAG26L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.



Laser Tag Label, Self-Laminating, 0.50" x .315" x .75", 156 Per Sheet, PET, White, 5000/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 594-26105                                                                                                                                                                                                                                                                                                                                                             |
| Type                | TAG26L                                                                                                                                                                                                                                                                                                                                                                |
| Color               | White (WH)                                                                                                                                                                                                                                                                                                                                                            |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                                  |
| Product Description | HellermannTyton’s self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification. |

|                                 |                                                                                             |
|---------------------------------|---------------------------------------------------------------------------------------------|
| Short Description               | Laser Tag Label, Self-Laminating, 0.50" x .315" x .75", 156 Per Sheet, PET, White, 5000/pkg |
| Global Part Name                | TAG26L-105-WH                                                                               |
| Width W (Imperial)              | 0.5                                                                                         |
| Width W (Metric)                | 12.7                                                                                        |
| Bundle Diameter Min (Imperial)  | 0.11                                                                                        |
| Bundle Diameter Min (Metric)    | 2.79                                                                                        |
| Bundle Diameter Max (Imperial)  | 0.12                                                                                        |
| Bundle Diameter Max (Metric)    | 3.17                                                                                        |
| Thickness T (Metric)            | 35.0                                                                                        |
| Width of Liner (Metric)         | 215.00                                                                                      |
| Width of Liner (Imperial)       | 8.5                                                                                         |
| Outside Diameter Max (Imperial) | 0.118                                                                                       |
| Outside Diameter Min (Metric)   | 1.5                                                                                         |
| Outside Diameter Min (Imperial) | 0.059                                                                                       |
| Outside Diameter Max (Metric)   | 3.00                                                                                        |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Material                       | Type 105, Polyester, white (105)  |
| Material Shortcut              | 105                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | No                                |
| UV Resistant (Yes/No)          | No                                |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33)   | Yes                               |
| ROHS Compliant                 | Yes                               |
| Package Quantity (Imperial)    | 5000                              |
| Package Quantity (Metric)      | 5000                              |
| Customs Number                 | 3919905060                        |
| Labels per Column              | 16                                |
| Labels per Row                 | 16                                |

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)