

# PRODUCT DATA SHEET

Molded Style Control Transformer

Cat. Number: C2M0050MLI-1

Rating: 50VA  
Phase: 1  
Freq: 50/60 Hz  
Temp. Rise: 80°C  
Enclosure: Core & Coil  
Material: Copper  
Ins. Class: 130°C

| DIMENSIONS |     |       |
|------------|-----|-------|
|            | in  | mm    |
| Height     | 4.4 | 79.4  |
| Width      | 3.3 | 83    |
| Depth      | 4.1 | 104.7 |

|        | lbs | kg  |
|--------|-----|-----|
| Weight | 2.5 | 1.1 |

| PRIMARY     |                | SECONDARY   |                |
|-------------|----------------|-------------|----------------|
| Voltage     | 208/230/460    | Voltage     | 24/115         |
| Connection  | Series (V)     | Connection  | Series (V)     |
| Termination | Terminal Block | Termination | Terminal Block |

|                                    |                           |
|------------------------------------|---------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 95 VA   |
|                                    | 10% Voltage Drop @ 125 VA |
|                                    | 15% Voltage Drop @ 150 VA |
| Full Load Watts Loss               | 15 Watts                  |

|                   |            |
|-------------------|------------|
| Country of Origin | Mexico     |
| Certifications    | UL: E50394 |