HUBBELL
Wiring Device-Kellems

# Locking Devices, Twist-Lock®, Safety Shroud, Shroud Kit for Plugs, 20A and 30A 3-Wire



By Hubbell Wiring Device-Kellems
Catalog # HBLSS3

Locking Devices, Twist-Lock®, Safety Shroud, Shroud Kit for Plugs, 20A and 30A 3-Wire

## Features

- Add-A-Shroud® devices allow conversion of existing 20A and 30A 3 to 5 wire Hubbell Insulgrip® Twist-Lock® devices to a Safety-Shroud® Twist-Lock® plug
- The Safety-Shroud® Twist-Lock® plug permits engagement with the Hubbell Mechanical Interlock Enclosure which virtually prevents make and break under load
- These devices provide a convenient and cost-effective way to convert existing Hubbell Insulgrip® Twist-Lock® plugs to Safety-Shroud® Twist-Lock® plugs

## Performance

Environmental - Flammability - HB or better, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact)

## Specifications

| | |
|---|---|
| Standards - RoHS Compliance Status | CM |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| EU RoHS Indicator | Contact Manufacturer |

## Conductor

| | |
|---|---|
| Number Of Wires | 3-Wire |
| Number Of Poles | 2-Pole |

## Dimensions

| | |
|---|---|
| Length | 2.04 in |
| Display Size | Standard Sized |
| Weight | 0.15 lb. |
| Height | 1.57 in |
| Width | 2.04 in |
| Dimensions | 2.04 in x 2.04 in x 1.57 in |

## General

| | |
|---|---|
| Color | White |
| Specifications | • Screws - Zinc plated steel<br>• Shroud - Nylon |
| UPC | 783585174136 |
| Type | Accessory |
| Item Type | Add-A-Shroud® |
| Material | Nylon |

## Logistics

| | |
|---|---|
| Carton Quantity | 10 |

## Operational

| | |
|---|---|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |

## Product Assets

Catalog [English]
Catalog Page [English]



© 2026 Hubbell Incorporated. All rights reserved