

Kellems Wire Management, Splicing Grips, Rotating Wire Rope Splicing, .44-.50"



By Hubbell Wiring Device-Kellems
Catalog # [03317001](#)

Kellems Wire Management, Splicing Grips, Rotating Wire Rope Splicing, .44-.50"

Features

- Galvanized steel meshes constructed in triple, double and single weave
- Rotating barrel helps eliminate twist in old rope being transferred to new rope

Application

Wire Rope Splicing

Performance

Mechanical - Approximate Breaking Strength - 5,000 (22,240),
Mechanical - Approximate Strength of Grip per Foot - 5.33 (1.63),
Mechanical - Barrel Dimensions - 3.00" (7.62) x .87" (2.21),
Mechanical - Working Load - (program formula 5% of Approximate Breaking Strength)

Specifications

Industry Standard(s)	CSA Certified
Environmental Conditions	No Limitations
EU RoHS Indicator	Yes

Conductor

Cable Size	0.44"-0.50" (1.11-1.27)
Cable Diameter Range	0.44 in-0.50 in
Number Of Conductors	1

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Force Related

Approx Breaking Strength	5,000 lb.
--------------------------	-----------

General

Specifications	<ul style="list-style-type: none">• Bushing - Steel• Lug - Steel• Shoulderss - Aluminum• Strand - Galvanized Steel• Swivel - Steel• Tag - Mylar• Tube - Steel
Color	Metallic
Style	Closed Mesh, Triple, Double, Single Weave
UPC	783585317212
Type	Rotating Wire Rope
Material - Mounting Hardware	On Cable Ends
Material	Steel, Galvanized
Series	Wire Rope Grips Series

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)