

Dust-Tight Strain Relief Grips

Aluminum Fittings, Galvanized Steel Mesh for Insulated Cables

IMPORTANT:

Read all breaking strength, safety and technical data relating to this product.
Refer to pages Y-60 through Y-67.



Non-Insulated, Wide Range Strain Relief

Thread Size	Cord Diameter Range Inches (cm)		Mesh Length @ Nom. Dia. Inches (cm)	Catalog Number
1/2 NPT	.24"-.32"	(.61-.81)	3.25" (8.25)	073031200 073031201 073031202
	.32"-.43"	(.81-1.09)	3.75" (9.52)	
	.43"-.54"	(1.09-1.37)	4.75" (12.06)	
3/4 NPT	.54"-.73"	(1.37-1.85)	6.5" (16.51)	073031203A
1 NPT	.73"-.97"	(1.85-2.46)	7" (17.78)	073031204
1-1/4 NPT	.97"-1.25"	(2.46-3.17)	9" (22.86)	073031205
PG29*	.73"-.97"	(1.85-2.46)	7" (17.78)	073PG291204

Note: *Panzergerwinde.



Insulated, Wide Range Strain Relief with Insulating Bushing

Thread Size	Cord Diameter Range Inches (cm)		Mesh Length @ Nom. Dia. Inches (cm)	Dim. A Inches (cm)	Min. Space Between Grips Inches (cm)	Catalog Number
1/2 NPS	.24"-.32"	(.61-.81)	3.25" (8.25)	1" (2.54)	1.25" (3.17)	073031206 073031207 073031208
	.32"-.43"	(.81-1.09)	3.75" (9.52)	1" (2.54)	1.25" (3.17)	
	.43"-.54"	(1.09-1.37)	4.75" (12.06)	1" (2.54)	1.25" (3.17)	
3/4 NPS	.54"-.73"	(1.37-1.85)	6.5" (16.51)	1" (2.54)	1.5" (3.81)	073031209A
1 NPS	.73"-.97"	(1.85-2.46)	7" (17.78)	1.313" (3.02)	1.75" (4.44)	073031210
1-1/4 NPS	.97"-1.25"	(2.46-3.17)	9" (22.86)	1.313" (3.02)	2.25" (5.71)	073031211
1-1/2 NPT	1.25"-1.50"	(3.17-3.81)	11.75" (29.84)	1.313" (3.02)	2.5" (6.35)	073031212
2 NPT	1.50"-1.70"	(3.81-4.32)	13.25" (33.65)	1.375" (3.49)	3.25" (8.25)	073031213
2-1/2 NPT	1.70"-2.00"	(4.32-5.08)	13.5" (34.29)	1.5" (3.81)	3.625" (9.21)	073031214 073031215
	2.00"-2.45"	(5.08-6.22)	13.75" (34.92)	1.5" (3.81)	3.625" (9.21)	



Dimensions in Inches (mm)