Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables

IMPORTANT:

Read all breaking strength, safety and technical data relating to this product.

Refer to pages Y-60 through Y-67.

Straight Female Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)		Form Size	Catalog Number
1/2	.375"-.500" .500"-.625"	(.95-1.27) (1.27-1.59)	F2	**07401043** **07401045**
3/4	.500"-.625"	(1.27-1.59)	F2	**07401052**
3/4	.625"-.750"	(1.59-1.90)	F4	**07401053**



90° Male Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)		Form Size	Catalog Number
3/8	.250"-.312" .312"-.375" .375"-.437"	(.63-.79) (.79-.95) (.95-1.11)	F1	**07401071** **07401072** **07401073**
1/2	.187"-.250" .250"-.375" .375"-.500" .500"-.625"	(.47-.63) (.63-.95) (.95-1.27) (1.27-1.59)	F2	**07401074** **07401076** **07401078** **07401080***
3/4	.375"-.500" .500"-.625" .625"-.750" .750"-.875"	(.95-1.27) (1.27-1.59) (1.59-1.90) (1.90-2.22)	F3	**07401081** **07401083** **07401084*** **074011275***
1	.500"-.625" .625"-.750" .750"-.875" .875"-1.000" 1.000"-1.125"	(1.27-1.59) (1.59-1.90) (1.90-2.22) (2.22-2.54) (2.54-2.86)	F4	**07401085** **07401087** **07401089** **07401091*** **074011229***
1-1/4	.750"-.875" .875"-1.000" 1.000"-1.125" 1.125"-1.250" 1.250"-1.375"	(1.90-2.22) (2.22-2.54) (2.54-2.86) (2.86-3.17) (3.18-3.51)	F5	**074011230** **07401137** **07401108** **074011042*** **074011043**
1-1/2	1.000"-1.125" 1.125"-1.250" 1.250"-1.375"	(2.54-2.86) (2.86-3.17) (3.17-3.49)	F5	**074011045** **074011046** **074011047**
2	1.312"-1.437" 1.437"-1.562" 1.562"-1687" 1.687"-1.812" 1.750"-1.875"	(3.33-3.65) (3.65-3.97) (3.96-4.29) (4.28-4.60) (4.44-4.76)	F6	**074011233** **074011244** **074011245** **074011246** **074011234***



45° Male Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)		Form Size	Catalog Number
1/2	.250"-.375" .375"-.500" .500"-.625"	(.63-.95) (.95-1.27) (1.27-1.59)	F2	**074011236** **074011021** **074011237***
3/4	.500"-.625" .625"-.750" .750"-.875"	(1.27-1.59) (1.59-1.90) (1.90-2.22)	F3	**074011049** **074011051*** **074011239***
1	.625"-.750" .750"-.875" .875"-1.000"	(1.59-1.90) (1.90-2.22) (2.22-2.54)	F4	**074011055** **074011057** **074011199***
1-1/4	1.000"-1.125" 1.125"-1.250"	(2.54-2.86) (2.86-3.17)	F5	**074011059** **074011060**



Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).

**Cable jacket may have to be stripped to pass through connector body.*

Dimensions in Inches (mm)