

Switches and Lighting Controls, Hubbell-
PRO Series, Toggle Switches, General
Purpose AC, Three Way, 15A 120/277V AC,
Back and Side Wired, Brown

By Hubbell Wiring Device-Kellems
Catalog # 1203B

Switches and Lighting Controls, Hubbell- PRO Series, Toggle
Switches, General Purpose AC, Three Way, 15A 120/277V AC,
Back and Side Wired, Brown

Features

- Steel, zinc plated bridge is corrosion resistant
- Color Coded by Amperage makes inspection easy even when installed
- Strip gauge for accurate wiring

Application

Back and Side Wired

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum for 1 minute, Electrical - Max. Continuous Current - 15A, Electrical - Max. Working Voltage - 277V AC, Electrical - Overload - Minimum 4.8 times rated current for 100 cycles, Electrical - Temperature Rise - 30°C maximum at rated current, Environmental - Flammability - UL 94V-2, Environmental - Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact, Mechanical - Terminal Accommodations - #14 AWG min. - #10 AWG max. solid and stranded copper wire only

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Single Pole

Current

Amperage Rating	15 A
Voltage Rating Description	120-277 VAC
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current



Connectivity	Back and Side Wired
Current / Amperage Rating	15 A

Dimensions

Length	4.18 in
Weight	0.15 lb.
Height	1.83 in
Width	1.49 in
Dimensions	4.18 in x 1.49 in x 1.83 in

General

Color	Brown
Style	Three Way
Series	Heavy Duty
Specifications	• Auto Grounding Mounting Bridge - Zinc Plated Steel • Base Material - Thermoplastic, Black • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Terminal Screws - Brass • Toggle Material - Nylon • Top Material - Thermoplastic, Blue
UPC	783585835181
Type	Toggle

Logistics

Carton Quantity	10
-----------------	----

Operational

Action	SPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish\]](#)