

Straight Blade Devices, Decorator Duplex
Receptacle, Hospital Grade, Hubbell-Pro,
15A 125V, 2-Pole 3-Wire Grounding, 5-15R,
Brown

By Hubbell Wiring Device-Kellems
Catalog # [2172](#)

Straight Blade Devices, Decorator Duplex Receptacle, Hospital
Grade, Hubbell-Pro, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R,
Brown

Features

- Triple wipe contacts
- High impact resistant decorator face
- Steel mounting strap

Application

Hubbell-Pro Heavy Duty Hospital Grade

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94V-2, Environmental - Operating Temperature - Maximum
continuous 75°C, minimum -40°C (w/o impact), Mechanical -
Product Identification - Ratings are a permanent part of the
device, Mechanical - Terminal Accommodation - #14-#10 AWG
copper stranded or solid conductor only, Mechanical - Terminal
Identification - Terminals identified in accordance with UL 498
and CSA

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	15 A
Voltage Rating	125 VAC
Wattage	1875 W
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.15 in
Width	1.57 in
Dimensions	3.28 in x 1.57 in x 1.15 in

General

Color	Brown
Style	Style Line decorator
Series	Hubbell-Pro
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - PBT • Clamping Plate - Plated steel • Face - Nylon • Ground Contacts - Brass • Mounting Screws - Zinc plated steel • Mounting Strap - Galvalized steel • Power Contacts - Brass
UPC	783585196657
Type	Duplex Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Style Line Decorator Duplex
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)



A Hubbell brand