

## Deluxe Cord Grips

Nylon Fittings, Non-Metallic Mesh, and Stainless Steel Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

### IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages W-61 through W-68.



### Nylon Fittings Non-Metallic Mesh, Liquidtight for Insulated Cables Straight Male Thread

| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number |
|------------------------|---------------------------------|-----------|----------------|
| 3/8                    | .187"-.250" (.47-.63)           | F1        | <b>CG304NM</b> |
|                        | .250"-.312" (.63-.79)           |           | <b>CG305NM</b> |
|                        | .312"-.375" (.79-.95)           |           | <b>CG306NM</b> |
| 1/2                    | .187"-.250" (.47-.63)           | F2        | <b>CG404NM</b> |
|                        | .250"-.375" (.63-.95)           |           | <b>CG406NM</b> |
|                        | .375"-.500" (.95-1.27)          |           | <b>CG408NM</b> |
| 3/4                    | .375"-.500" (.95-1.27)          | F3        | <b>CG608NM</b> |
|                        | .500"-.625" (1.27-1.59)         |           | <b>CG610NM</b> |
|                        | .625"-.750" (1.59-1.90)         |           | <b>CG612NM</b> |
| 1                      | .500"-.625" (1.27-1.59)         | F4        | <b>CG810NM</b> |
|                        | .625"-.750" (1.59-1.90)         |           | <b>CG812NM</b> |
|                        | .750"-.875" (1.90-2.22)         |           | <b>CG814NM</b> |
|                        | .875"-.1.000" (2.22-2.54)       |           | <b>CG816NM</b> |



### 90° Male Thread

| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number   |
|------------------------|---------------------------------|-----------|------------------|
| 1/2                    | .250"-.375" (.63-.95)           | F2        | <b>CG40690NM</b> |
|                        | .375"-.500" (.95-1.27)          |           | <b>CG40890NM</b> |
| 3/4                    | .375"-.500" (.95-1.27)          | F3        | <b>CG60890NM</b> |
|                        | .500"-.625" (1.27-1.59)         |           | <b>CG61090NM</b> |
| 1                      | .625"-.750" (1.59-1.90)         | F4        | <b>CG81290NM</b> |
|                        | .750"-.875" (1.90-2.22)         |           | <b>CG81490NM</b> |

### Stainless Steel Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables Straight Male Thread

| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number  |
|------------------------|---------------------------------|-----------|-----------------|
| 1/2                    | .187"-.250" (.47-.63)           | F2        | <b>CG404SST</b> |
|                        | .250"-.375" (.63-.95)           |           | <b>CG406SST</b> |
|                        | .375"-.500" (.95-1.27)          |           | <b>CG408SST</b> |
|                        | .500"-.625" (1.27-1.59)         |           | <b>CG410SST</b> |
| 3/4                    | .375"-.500" (.95-1.27)          | F2        | <b>CG608SST</b> |
|                        | .500"-.625" (1.27-1.59)         |           | <b>CG610SST</b> |
| 3/4                    | .625"-.750" (1.59-1.90)         | F3        | <b>CG612SST</b> |
|                        | .750"-.875" (1.90-2.22)         |           | <b>CG614SST</b> |
| 1                      | .500"-.625" (1.27-1.59)         | F4        | <b>CG810SST</b> |
|                        | .625"-.750" (1.59-1.90)         |           | <b>CG812SST</b> |
|                        | .750"-.875" (1.90-2.22)         |           | <b>CG814SST</b> |
|                        | .875"-.1.000" (2.22-2.54)       |           | <b>CG816SST</b> |

Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).

\*Cable jacket may have to be stripped to pass through connector body.



Dimensions in Inches (mm)