

Strain Relief for Liquidtight Conduit

Steel Fitting, Stainless Steel Mesh for Liquidtight Metal Conduit and PolyTuff® I Non-Metallic Conduit.

IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages W-61 through W-68.



Straight With Chase Fitting

Conduit Trade Size Inches	NPT Fitting Size Inches	Mesh Length Inches (cm)		Catalog Number
1/2	1/2	3.5"	(8.89)	07406079
3/4	3/4	4"	(10.16)	07406080
1	1	5"	(12.70)	07406081
1 1/4	1 1/4	6"	(15.24)	07406082
1 1/2	1 1/2	6.75"	(17.14)	07406083



45° Angle With Male Fitting

Conduit Trade Size Inches	NPT Fitting Size Inches	Mesh Length Inches (cm)		Catalog Number (Insulated)
3/8	1/2	3"	(7.62)	074093561
1/2	1/2	3.5"	(8.89)	074093562
3/4	3/4	4"	(10.16)	074093563
1	1	5"	(12.70)	074093564
1 1/4	1 1/4	6"	(15.24)	074093565
1 1/2	1 1/2	6.75"	(17.14)	074093566
2	2	8"	(20.32)	074093568

Note: For use with Liquidtight Metal conduit and PolyTuff® I Non-Metallic conduit.