

## Low Profile Devices

Rating					Devices		Cord Diameter	
Amps	Poles and Wires	Configuration Recep./ Plug/ Conn. Inlet	AC Voltage	Plug	Receptacle	Min. Inches	Max. Inches (mm)	
20	3P 4W		3Ø 250V			.350"	.710" (8.3 - 15.9)	
30	3P 4W		125/250V	<b>L430P12</b>	<b>L430R12</b>	.390"	.775" (9.9 - 19.7)	
30	3P 4W		3Ø 250V	<b>L430P9</b>	<b>L430R9</b>	.390"	.775" (9.9 - 19.7)	
60	3P 4W		3Ø 250V	<b>A460P9</b>	<b>A460R9</b> With Cover: <b>A460R9KIT</b>	.75"	1.25" (19.1 - 31.8)	
60	4P 5W		3ØY 120/208V	<b>A560P9</b>	<b>HBL560R9W</b>	.89"	1.42" (22.6 - 36.1)	
100	4P 5W		3ØY 120/208V	<b>A5100P9</b>	<b>HBL5100R9W</b>	1.34"	1.50" (34.0 - 38.1)	

## Specifications

Electrical	
Dielectric Withstand Voltage	3000V AC
Max. Working Voltage	250V RMS
Current Interrupting	Certified for current interruption at full rated current.
Temperature Rise	Max. 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Endurance	Up to 5,000 connect and disconnect cycles at full rated current and voltage.
Mechanical	
Impact Resistance	Per CSA C22.2 No. 182.1 / UL1682
Cord Grip Cable Retention	Per CSA C22.2 No. 182.1 / UL1682
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL standard 62, CSA C22.2 No. 49 and the <HAR> European Standards.
Terminal Identification	Terminals identified in accordance with North American convention.
Product Identification	Ratings are a permanent part of the device housing.
Environmental	
Flammability	HB or better per UL94 or CSA C22.2 No. 0.17
Ingress Protection	IP22 Suitability
Operating Temperatures	Maximum Continuous 75° C; Minimum -40°C without impact

## Application Guide

Agriculture	Indoor location and maintenance.
Chemical Processing	Indoor location and maintenance.
Construction	Indoors for added safety and abuse resistance.
Entertainment	Indoor location and maintenance.
Food Service	Food service areas where aesthetics and space are concerns.
Light Manufacturing	Indoor locations and maintenance.
Manufacturing	Light assembly areas, stamping operations and maintenance areas.
Military	Warehouse and maintenance areas.

## Materials

Plug	Material
Case	PBT
Shroud	PBT
Pin Carrier 20 & 30A	PBT
Pin and Carrier 60A	High-Impact Thermoset
Pins	Brass CDA#360
Assembly Screws	Stainless Steel (300 series)
Terminal Screws	Stainless Steel (300 series)
Receptacle	
Body	PBT
Sleeve Carrier 20 & 30A	PBT
Sleeve Carrier 60A	High-Impact Thermoset
Sleeves	Brass CDA #360
Assembly Screws	Stainless Steel (300 series)
Terminal Screws	Stainless Steel (300 series)
Adapter Plate 20 & 30A	Galvanized Steel
Adapter Plate 60A	Aluminum
Wall Trim Plate	PBT
Panel Mount Trim Plate	Stainless Steel (300 series)

Note: See page G-29 for product dimensions.